## NSN 5950-01-352-6871

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-352-6871

| Delichility Indicator.   |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Reliability Indicator:   |  |  |  |  |  |  |
| Not established  |  |  |  |  |  |  |
| Turn Quantity:   |  |  |  |  |  |  |
| 36 single component single winding   |  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                    |  |  |  |  |  |  |
| 2.500 inches single mounting facility single center group                                    |  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                     |  |  |  |  |  |  |
| 1.750 inches single mounting facility single center group                                    |  |  |  |  |  |  |
| Inductance Type:   |  |  |  |  |  |  |
| Fixed  |  |  |  |  |  |  |
| Inductance Rating:   |  |  |  |  |  |  |
| 2.80 microhenries single component single winding  |  |  |  |  |  |  |
| Body Length:   |  |  |  |  |  |  |
| 3.000 inches   |  |  |  |  |  |  |
| Body Width:  |  |  |  |  |  |  |
| 2.250 inches   |  |  |  |  |  |  |
| Body Height:   |  |  |  |  |  |  |
| 1.350 inches   |  |  |  |  |  |  |
| Maximum Operating Temp:  |  |  |  |  |  |  |
| 90.0 degrees celsius   |  |  |  |  |  |  |
| Winding Quantity:  |  |  |  |  |  |  |
| 1 single component   |  |  |  |  |  |  |
| Inclosure Type:  |  |  |  |  |  |  |
| Fully enclosed   |  |  |  |  |  |  |
| Mounting Facility Quantity:  |  |  |  |  |  |  |
| 4 single group   |  |  |  |  |  |  |
| Mounting Method:   |  |  |  |  |  |  |
| Threaded hole single group   |  |  |  |  |  |  |
| Rating Method:   |  |  |  |  |  |  |
| Electrical single component single winding and winding turns single component single winding |  |  |  |  |  |  |
| Thread Size:   |  |  |  |  |  |  |
| 0.138 inches single group  |  |  |  |  |  |  |
| Winding Conductor Size:  |  |  |  |  |  |  |
| 0.04030 inches american wire gage single component single winding                            |  |  |  |  |  |  |
| Winding Operating Current:   |  |  |  |  |  |  |
| 14.1 amperes dc single component single winding  |  |  |  |  |  |  |
| Dc Resistance Rating In Ohms:  |  |  |  |  |  |  |
| 0.120 single component single winding  |  |  |  |  |  |  |
| Thread Series Designator:  |  |  |  |  |  |  |
| Unc single group   |  |  |  |  |  |  |

2 turret

**Terminal Type And Quantity:** 

## NSN 5950-01-352-6871

Reactor - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0