

View Online at <https://aerobasegroup.com/nsn/5950-01-354-4735>

Reliability Indicator:

Not established

Turn Quantity:

20 1st component 1st secondary

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.900 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Overall Height:

1.400 inches

Inductance Rating:

8.50 microhenries 1st component 1st secondary

Frequency Rating:

100.0 kilohertz 2nd component

Input-output Phase Relationship:

Single phase to single phase 2nd component

Winding Shielding Method:

Internal shield connected to secondary terminal 2nd component

Body Length:

3.400 inches

Body Width:

2.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Winding turns 1st component 2nd primary

Winding Function And Quantity:

2 primary 2nd component and 3 secondary 2nd component

Thread Size:

0.112 inches single group

Winding Conductor Size:

0.01594 inches american wire gage 1st component 2nd secondary

Dc Resistance Rating In Ohms:

0.150 1st component 2nd secondary

Special Features:

Internal shield brought out and connected to primary terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0