

View Online at <https://aerobasegroup.com/nsn/5950-01-356-4239>

Reliability Indicator:

Not established

Overall Length:

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.147 inches single mounting facility single center group and 1.227 inches single mounting facility single center group

Overall Height:

2.750 inches

Overall Width:

1.562 inches

Mounting Hole Diameter:

0.218 inches 1st group and 0.221 inches 1st group 0.250 inches 2nd group and 0.260 inches 2nd group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component and three phase to six phase single component and three phase to single phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to inclosure single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 all groupings

Mounting Method:

Unthreaded hole all groupings

Winding Function And Quantity:

3 primary 3rd component and 8 secondary 3rd component

Winding Operating Current:

2.0 amperes ac single component 1st secondary 0.1 amperes ac single component 2nd secondary 0.25 amperes ac single component 3rd secondary 0.33 amperes ac single component 4th secondary

Winding Operating Voltage:

7.50 ac pounds per hour wet single component 1st secondary 11.40 ac pounds per hour wet single component 2nd secondary 11.40 ac pounds per hour wet single component 3rd secondary 20.10 ac pounds per hour wet single component 4th secondary 208.00 ac pounds per hour wet single component all primary

Special Features:

Three primary windings; 8 secondary windings

Terminal Type And Quantity:

37 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A058b0