

View Online at <https://aerobasegroup.com/nsn/5950-01-357-4205>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Overall Length:**

10.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

7.280 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.380 inches single mounting facility single center group

**Overall Height:**

5.300 inches

**Overall Width:**

5.700 inches

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-delta

**Maximum Transformer Power Rating:**

900.0 volt-ampere single component

**Maximum Operating Temp:**

50.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

4.5 amperes ac single component single secondary

**Winding Power Rating:**

720.0 watts single component single secondary

**Winding Operating Voltage:**

116.00 ac volts single component single secondary

**Test Data Document:**

11447-10037869 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0