

View Online at <https://aerobasegroup.com/nsn/5950-01-357-4205>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

10.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.280 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.380 inches single mounting facility single center group

Overall Height:

5.300 inches

Overall Width:

5.700 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Transformer Power Rating:

900.0 volt-ampere single component

Maximum Operating Temp:

50.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

4.5 amperes ac single component single secondary

Winding Power Rating:

720.0 watts single component single secondary

Winding Operating Voltage:

116.00 ac volts single component single secondary

Test Data Document:

11447-10037869 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0