## NSN 5950-01-357-7072

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-357-7072

| Reliability Indicator:   |
|--|
| Not established  |
| Turn Quantity:   |
| 11 single component single primary   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                    |
| 1.732 inches single mounting facility single center group                                    |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                     |
| 1.000 inches single mounting facility single center group                                    |
| Inductance Rating:   |
| 110.00 microhenries single component single primary  |
| Frequency Rating:  |
| 100.0 kilohertz single component   |
| Body Length:   |
| 1.800 inches   |
| Body Outside Diameter:   |
| 3.040 inches   |
| Maximum Operating Temp:  |
| 60.0 degrees celsius   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded hole single group   |
| Rating Method:   |
| Electrical single component single primary and winding turns single component single primary |
| Winding Function And Quantity:   |
| 1 primary single component and 1 secondary single component                                  |
| Thread Size:   |
| 0.190 inches single group  |
| Winding Conductor Size:  |
| 0.06408 inches american wire gage single component single secondary                          |
| Thread Series Designator:  |
| Unf single group   |
| Terminal Type And Quantity:  |
| 4 pin  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |

No

## NSN 5950-01-357-7072

Radio Frequency Transformer - Page 2 of 2



Fiig:

A058b0