

View Online at <https://aerobasegroup.com/nsn/5950-01-357-9483>

Reliability Indicator:

Not established

Overall Length:

3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Overall Height:

2.906 inches

Overall Width:

2.594 inches

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Winding Operating Current:

500.0 milliamperes dc single component 1st secondary 500.0 milliamperes dc single component 2nd secondary 700.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

28.00 dc pounds per hour wet single component 1st secondary 28.00 dc pounds per hour wet single component 2nd secondary 10.00 dc pounds per hour wet single component 3rd secondary 115.00 ac pounds per hour wet single component single primary 115.00 ac pounds per hour wet single component all primary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0