NSN 5950-01-359-1806

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-359-1806

| Turn Quantity: 100 single component 1st winding25 single component 2nd winding25 single component 3rd winding5 single component 4th winding Inductance Rating: 20.00 millithenites single component 1st winding Body Length: 0.531 inches Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding De Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 3rd winding0.700 single component 3r | |
|--|--|
| Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | bility Indicator: |
| Inductance Rating: 20.00 millihenries single component 1st winding25 single component 2nd winding25 single component 3rd winding5 single component 4th winding Body Length: 0.531 inches Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.700 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | stablished |
| Inductance Rating: 20.00 millihenries single component 1st winding Body Length: 0.531 inches Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 4th winding Do Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | Quantity: |
| 20.00 millihenries single component 1st winding Body Length: 0.531 inches Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Ellectrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 4th winding De Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 3rd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | single component 1st winding25 single component 2nd winding25 single component 3rd winding5 single component 4th winding |
| Body Length: 0.531 inches Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding De Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | ctance Rating: |
| 0.531 inches Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | millihenries single component 1st winding |
| Body Width: Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | Length: |
| Between 0.481 inches and 0.503 inches Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.00631 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | inches |
| Body Height: 0.720 inches Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | Width: |
| Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding 0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | een 0.481 inches and 0.503 inches |
| Maximum Operating Temp: 110.0 degrees celsius Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding 0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 2nd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | Height: |
| Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: |) inches |
| Winding Quantity: 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | mum Operating Temp: |
| 4 single component Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.00631 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | degrees celsius |
| Inclosure Type: Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | ling Quantity: |
| Fully enclosed Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | gle component |
| Mounting Method: Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | sure Type: |
| Clamp single group Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | enclosed |
| Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | nting Method: |
| Rating Method: Electrical single component all winding and winding turns single component all winding Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.0063 inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | p single group |
| Winding Conductor Size: 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.00633 inches american wire gage single component 2nd winding0.00633 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | g Method: |
| 0.00631 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.00633 inches american wire gage single component 2nd winding0.00633 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | rical single component all winding and winding turns single component all winding |
| inches american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | ling Conductor Size: |
| Dc Resistance Rating In Ohms: 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | 31 inches american wire gage single component 1st winding0.00631 inches american wire gage single component 2nd winding0.00631 |
| 2.500 single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th winding Terminal Type And Quantity: 8 pin Shelf Life: | s american wire gage single component 3rd winding0.02010 inches american wire gage single component 4th winding |
| winding Terminal Type And Quantity: 8 pin Shelf Life: | esistance Rating In Ohms: |
| Terminal Type And Quantity: 8 pin Shelf Life: | single component 1st winding0.700 single component 2nd winding0.700 single component 3rd winding0.050 single component 4th |
| 8 pin Shelf Life: | ng |
| Shelf Life: | inal Type And Quantity: |
| | |
| N/a | Life: |
| N/a | |
| Unit Of Measure: | Of Measure: |
| | |
| Demilitarization: | ilitarization: |
| No | |
| Fiig: | |
| A058b0 | b0 |