## NSN 5950-01-359-4852

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-359-4852

## **Reliability Indicator:**

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

## **Overall Length:**

Between 1.440 inches and 1.500 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.100 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.800 inches single mounting facility single center group

## **Overall Height:**

Between 1.169 inches and 1.450 inches

#### **Overall Width:**

Between 1.190 inches and 1.250 inches

#### Inductance Type:

Fixed

#### Inductance Rating:

20.00 microhenries single component all winding and 30.00 microhenries single component all winding

#### **Frequency Rating:**

30.0 kilohertz single component

## Maximum Operating Temp:

85.0 degrees celsius

#### Winding Quantity:

2 single component

## Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Threaded hole single group

#### **Rating Method:**

Electrical single component all winding

#### **Thread Size:**

0.112 inches single group

## Winding Operating Current:

2.0 amperes dc single component all winding and 40.0 amperes dc single component all winding

## Dc Resistance Rating In Ohms:

10.000 single component all winding

## **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

4 pin

# NSN 5950-01-359-4852

Reactor - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

