NSN 5950-01-359-4852

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-359-4852

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

Between 1.440 inches and 1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.100 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.800 inches single mounting facility single center group

Overall Height:

Between 1.169 inches and 1.450 inches

Overall Width:

Between 1.190 inches and 1.250 inches

Inductance Type:

Fixed

Inductance Rating:

20.00 microhenries single component all winding and 30.00 microhenries single component all winding

Frequency Rating:

30.0 kilohertz single component

Maximum Operating Temp:

85.0 degrees celsius

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component all winding

Thread Size:

0.112 inches single group

Winding Operating Current:

2.0 amperes dc single component all winding and 40.0 amperes dc single component all winding

Dc Resistance Rating In Ohms:

10.000 single component all winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 pin

NSN 5950-01-359-4852

Reactor - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0