NSN 5950-01-360-8728

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-360-8728

Not established Turn Quantity: 7 single component all winding Inductance Type: Fixed Inductance Rating: 12.00 microhenries single component all winding Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes de single component all winding C Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a Unit Of Measure:	Daliahilita Indicator
Turn Quantity: 7 single component all winding Inductance Type: Fixed Inductance Rating: 12.00 microhenries single component all winding Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Length: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes de single component all winding Thread Seties Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Reliability Indicator:
7 single component all winding Inductance Type: Fixed Inductance Rating: 12.00 microhenries single component all winding Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Inductance Type: Fixed Inductance Rating: 12.00 microhenries single component all winding Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	-
Fixed Inductance Rating: 12.00 microhenries single component all winding Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Inductance Rating: 12.00 microhenries single component all winding Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Inpedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Impedance Rating In Ohms: 175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	-
175.0 single component all winding Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Body Length: 0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
0.340 inches Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Body Outside Diameter: 0.700 inches Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Maximum Operating Temp: 85.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Winding Quantity: 2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
2 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Winding Quantity:
Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	
Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Inclosure Type:
1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Fully enclosed
Mounting Method: Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Mounting Facility Quantity:
Threaded hole single group Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	1 single group
Rating Method: Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Mounting Method:
Electrical single component all winding and winding turns single component all winding Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Threaded hole single group
Thread Size: 0.112 inches single group Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Rating Method:
O.112 inches single group Winding Conductor Size: O.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Electrical single component all winding and winding turns single component all winding
Winding Conductor Size: 0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Thread Size:
0.01594 inches american wire gage single component all winding Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	0.112 inches single group
Winding Operating Current: 12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Winding Conductor Size:
12.0 amperes dc single component all winding Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	0.01594 inches american wire gage single component all winding
Dc Resistance Rating In Ohms: 2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Winding Operating Current:
2.500 single component all winding Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	12.0 amperes dc single component all winding
Thread Series Designator: Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Dc Resistance Rating In Ohms:
Unc single group Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	2.500 single component all winding
Terminal Type And Quantity: 4 wire lead Shelf Life: N/a	Thread Series Designator:
4 wire lead Shelf Life: N/a	Unc single group
Shelf Life: N/a	Terminal Type And Quantity:
N/a	4 wire lead
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

--

NSN 5950-01-360-8728

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0