

View Online at <https://aerobasegroup.com/nsn/5950-01-361-4341>

Reliability Indicator:

Not established

Turn Quantity:

50 3rd component single winding

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.900 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Overall Height:

1.400 inches

Frequency Rating:

100.0 kilohertz 2nd component

Winding Shielding Method:

Internally shielded and brought out to primary terminal 2nd component

Body Length:

3.400 inches

Body Width:

2.000 inches

Maximum Operating Temp:

55.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical 3rd component single winding and winding turns 3rd component single winding

Winding Function And Quantity:

1 primary 2nd component

Features Provided:

Tinned wire leads

Thread Size:

0.112 inches single group

Winding Conductor Size:

0.00795 inches american wire gage 3rd component single winding

Winding Operating Current:

16.0 amperes ac 2nd component single primary

Dc Resistance Rating In Ohms:

0.150 3rd component single winding

Winding Operating Voltage:

7.70 ac volts 1st component single primary

Special Features:

2nd component, current transformer, secondary rated but not included

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0