

View Online at <https://aerobasegroup.com/nsn/5950-01-362-3996>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Overall Length:**

0.815 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.585 inches single mounting facility single center group and 0.615 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.470 inches single mounting facility single center group and 0.530 inches single mounting facility single center group

**Overall Width:**

0.700 inches

**Inductance Rating:**

5.00 microhenries single component single primary

**Frequency Rating:**

40.0 kilohertz single component

**Winding Shielding Method:**

Internal shield connected to secondary terminal single component

**Body Height:**

0.400 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

300.0 milliamperes ac single component single primary

**Dc Resistance Rating In Ohms:**

3.600 single component single secondary

**Winding Operating Voltage:**

26.00 ac volts single component single secondary

**Test Data Document:**

99167-5908337 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

5 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0