NSN 5950-01-363-0825

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-363-0825

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.500 inches single mounting facility single center group |
| Frequency Rating: |
| 48.0 hertz single component and 66.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 5.250 inches |
| Body Width: |
| 4.500 inches |
| Body Height: |
| 3.500 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 2 primary single component and 6 secondary single component |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 1.1 amperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 64.00 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug and 18 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig:

A058b0