

View Online at <https://aerobasegroup.com/nsn/5950-01-363-2143>

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Inductance Rating:**

0.12 microhenries single component single winding

**Coil Form Type:**

Solid single component

**Core Construction:**

Solid single component

**Body Length:**

Between 0.240 inches and 0.260 inches

**Body Outside Diameter:**

Between 0.085 inches and 0.105 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding

**Winding Operating Current:**

1.27 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

0.090 single component single winding

**Quality Factor:**

40 single component single winding

**Test Data Document:**

81349--39010/08-br12kr specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire lead

**Specification Data:**

81349-mil-prf-39010 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0

**Mil-std (military Standard):**

Mil-prf-39010 spec.