

View Online at <https://aerobasegroup.com/nsn/5950-01-366-6066>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.938 inches single mounting facility single center group

Frequency Rating:

40.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.010 inches

Body Width:

1.320 inches

Body Height:

2.680 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

7.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

25.80 dc volts single component 4th secondary

Special Features:

One primary winding and six secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

19 turret and 6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0