

View Online at <https://aerobasegroup.com/nsn/5950-01-368-8132>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches all mounting facilities all center groupings

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

30.0 volt-ampere single component

Body Length:

2.690 inches

Body Width:

2.130 inches

Body Height:

3.500 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches all groupings

Winding Operating Current:

3.0 amperes ac single component single secondary

Winding Power Rating:

30.0 volts-amperes single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

5 wire hook

Specification Data:

81349-mil-t-27/320 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0