

View Online at <https://aerobasegroup.com/nsn/5950-01-369-0823>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.438 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches all mounting facilities all center groupings

Mounting Hole Diameter:

0.158 inches all groupings

Frequency Rating:

400.0 hertz all components

Input-output Phase Relationship:

Three phase to six phase single component

Winding Shielding Method:

Internal shield brought out to terminal all components

Body Length:

3.440 inches

Body Width:

2.680 inches

Body Height:

1.550 inches

Distance Between Mounting Facility Centers:

2.000 inches single mounting facili type 1st center group 2.438 inches single mounting facili type 2nd center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Unthreaded hole all groupings

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

55.0 milliamperes ac single component single primary

Winding Operating Voltage:

31.00 ac pounds per hour wet single component 1st secondary 31.00 ac pounds per hour wet single component 2nd secondary 20.00 ac pounds per hour wet single component 3rd secondary 200.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

13 wire lead

Specification Data:

99167-5909037 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0