

View Online at <https://aerobasegroup.com/nsn/5950-01-369-9021>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.260 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.760 inches all mounting facilities all center groupings

Frequency Rating:

50.0 kilohertz 2nd component

Input-output Phase Relationship:

Single phase to single phase all components

Winding Shielding Method:

Internal shield brought out to terminal 2nd component

Body Length:

4.800 inches

Body Width:

2.380 inches

Body Height:

2.380 inches

Maximum Operating Temp:

70.0 degrees celsius

Distance Between Mounting Facility Centers:

4.260 inches 1st mounting facility all center groupings

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

4 primary all components and 2 control all components and 8 secondary all components

Thread Size:

0.138 inches all groupings

Winding Operating Current:

3.3 amperes ac single component 1st secondary

Winding Operating Voltage:

26.00 ac volts single component 2nd primary and 35.00 ac volts single component 2nd primary

Special Features:

200: 1current transformer and flyback transformer

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

22 turret

Specification Data:

09004-34931 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0