

View Online at <https://aerobasegroup.com/nsn/5950-01-370-3537>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.875 inches single mounting facility all center groupings

Mounting Slot Width:

0.203 inches all groupings

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

150.0 volt-ampere single component

Body Length:

3.750 inches

Body Width:

3.625 inches

Body Height:

3.125 inches

Distance Between Mounting Facility Centers:

3.125 inches single mounting facili type 1st center group 2.875 inches single mounting facili type 2nd center group

Inclosure Type:

Open

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Slot all groupings

Winding Operating Current:

1.25 amperes ac single component single secondary

Winding Power Rating:

150.0 volts-amperes single component single winding

Winding Operating Voltage:

480.00 ac pounds per hour wet single component single primary 120.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0