

View Online at <https://aerobasegroup.com/nsn/5950-01-370-3538>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility all center groupings

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

3.188 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

2.297 inches single mounting facili type 1st center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded stud all groupings

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.164 inches all groupings

Winding Operating Current:

7.0 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0