

View Online at <https://aerobasegroup.com/nsn/5950-01-370-4857>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.120 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

50.0 volt-ampere single component

Body Length:

2.000 inches

Body Width:

1.620 inches

Body Height:

1.810 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

8.0 amperes ac single component all secondary

Winding Operating Voltage:

5.00 ac volts all components single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Specification Data:

81349-mil-t-27/335-01 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0