NSN 5950-01-371-3687

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-371-3687

| view Offiline at https://aerobasegroup.com/hist//0350-01-571-5007 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.490 inches single mounting facility single center group and 2.510 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.187 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Core grounded single component |
| Body Length: |
| 3.980 inches |
| Body Width: |
| 2.760 inches |
| Body Height: |
| 3.350 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Slot single group |
| Winding Function And Quantity: |
| 2 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 75.0 milliamperes ac single component all primary |
| Winding Operating Voltage: |
| 19.75 ac volts single component single secondary and 21.00 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 6 eyelet |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0