## NSN 5950-01-372-0240

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-372-0240

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.427 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.650 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.140 inches single group   |
| Inductance Rating:  |
| 259.00 microhenries single component single winding                       |
| Frequency Rating:   |
| 10.0 kilohertz single component   |
| Body Length:  |
| 1.710 inches  |
| Body Width:   |
| 1.090 inches  |
| Body Height:  |
| 0.940 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Rating Method:  |
| Electrical single component single winding                                |
| Winding Operating Current:  |
| 5.0 amperes dc single component single winding                            |
| Dc Resistance Rating In Ohms:   |
| 0.192 single component single winding                                     |
| Precious Material And Location:   |
| Terminals gold  |
| Precious Material:  |
| Gold  |
| Terminal Type And Quantity:   |
| 2 pin   |
| Shelf Life:   |

N/a

## NSN 5950-01-372-0240

Reactor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A058b0