

View Online at <https://aerobasegroup.com/nsn/5950-01-372-0997>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.813 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

100.0 volt-ampere single component

Body Length:

3.766 inches

Body Width:

3.375 inches

Body Height:

2.875 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

4.2 amperes ac single component single secondary

Winding Power Rating:

100.0 volts-amperes single component all winding

Winding Operating Voltage:

550.00 ac pounds per hour wet single component single primary 24.00 ac pounds per hour wet single component single secondary

Test Data Document:

07131-315-048507-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0