## NSN 5950-01-372-2021

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-372-2021

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.700 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.600 inches single mounting facility single center group                 |
| Overall Height:   |
| 3.110 inches  |
| Overall Width:  |
| 1.880 inches  |
| Mounting Slot Width:  |
| 0.240 inches single group   |
| Frequency Rating:   |
| 50.0 hertz single component or 400.0 hertz single component               |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 2.330 inches  |
| Body Width:   |
| 0.940 inches  |
| Body Height:  |
| 2.670 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Slot single group   |
| Winding Function And Quantity:  |
| 1 secondary single component  |
| Winding Operating Current:  |
| 50.0 amperes ac single component single primary                           |
| Terminal Type And Quantity:   |
| 2 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A058b0