## NSN 5950-01-373-5035

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-373-5035

view Offilite at https://aerobasegroup.com/nsi//0550-01-5/5-5055
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches single mounting facility single center group
Frequency Rating:
49.0 kilohertz all components and 51.0 kilohertz all components
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
1.550 inches
Body Width:
1.400 inches
Body Height:
1.550 inches
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
2 primary single component and 2 secondary single component
Thread Size:
0.112 inches single group
Winding Operating Current:
4.5 amperes ac single component 1st secondary
Winding Operating Voltage:
60.00 ac volts single component all primary
Test Data Document:
07690-635011 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
15 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5950-01-373-5035

Power Transformer - Page 2 of 2



Fiig:

A058b0