

View Online at <https://aerobasegroup.com/nsn/5950-01-373-5035>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Frequency Rating:

49.0 kilohertz all components and 51.0 kilohertz all components

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.550 inches

Body Width:

1.400 inches

Body Height:

1.550 inches

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

4.5 amperes ac single component 1st secondary

Winding Operating Voltage:

60.00 ac volts single component all primary

Test Data Document:

07690-635011 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0