

View Online at <https://aerobasegroup.com/nsn/5950-01-373-9854>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.000 inches

Body Width:

4.250 inches

Body Height:

2.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

40.0 amperes dc single component 1st secondary 1.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

187.00 ac pounds per hour dry single component single primary and 204.00 ac pounds per hour with retaining chain single component single primary

Special Features:

Thermal switch circuit included with transformer

Terminal Type And Quantity:

7 turret and 310 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0