

View Online at <https://aerobasegroup.com/nsn/5950-01-375-5059>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.105 inches single mounting facility single center group and 5.145 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.605 inches single mounting facility single center group and 4.645 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.040 inches

Body Width:

5.540 inches

Body Height:

3.510 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

850.0 milliamperes ac single component single primary

Winding Power Rating:

9.0 watts single component single primary

Winding Operating Voltage:

230.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0