NSN 5950-01-376-0922

Power Transformer - Page 1 of 2

N/a



| view Online at https://aerobasegroup.com/hsn/5950-01-376-0922 |
|---|
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 9.875 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 8.875 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 6.500 inches single mounting facility single center group |
| Overall Height: |
| 16.750 inches |
| Overall Width: |
| 11.750 inches |
| Mounting Hole Diameter: |
| 0.406 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 25.0 kilovolt-ampere single component |
| Maximum Operating Temp: |
| 50.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 55.6 amperes ac single component single primary |
| Winding Power Rating: |
| 25.0 kilovolt-amperes single component single winding |
| Winding Operating Voltage: |
| 450.00 ac volts single component single primary |
| Test Data Document: |
| 86301-1931-25 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 4 wire lead |
| Shalf Life: |

NSN 5950-01-376-0922

Power Transformer - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0