## NSN 5950-01-376-3007

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-376-3007
Reliability Indicator:
Not established
Turn Quantity:
28 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.418 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.418 inches single mounting facility single center group
Mounting Hole Diameter:
0.148 inches all groupings and 0.154 inches all groupings
Inductance Type:
Fixed
Inductance Rating:
45.00 microhenries single component single winding
Frequency Rating:
70.0 kilohertz single component
Body Length:
1.700 inches
Body Width:
1.700 inches
Body Height:
0.900 inches
Maximum Operating Temp:
100.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Winding turns single component single winding
Winding Conductor Size:
0.10164 inches american wire gage single component single winding
Test Data Document:
57957-c5118095 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 wire lead
Shelf Life:

N/a

## NSN 5950-01-376-3007

Reactor - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0