NSN 5950-01-376-3008

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-376-3008

Reliability Indicator:
Not established
Turn Quantity:
36 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.418 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.418 inches single mounting facility single center group
Mounting Hole Diameter:
0.148 inches single group and 0.154 inches single group
Inductance Rating:
130.00 microhenries single component single winding
Frequency Rating:
35.0 kilohertz single component
Body Length:
1.700 inches
Body Width:
1.700 inches
Body Height:
0.950 inches
Maximum Operating Temp:
125.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Winding turns single component single winding
Winding Conductor Size:
0.06408 inches american wire gage single component single winding
Test Data Document:
57957-c5118090 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-01-376-3008

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0