

View Online at <https://aerobasegroup.com/nsn/5950-01-380-0936>

Reliability Indicator:

Not established

Overall Length:

410.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

260.0 millimeters all mounting facilities 1st center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

165.0 millimeters all mounting facilities 1st center group

Overall Height:

267.0 millimeters

Overall Width:

173.0 millimeters

Mounting Hole Diameter:

16.0 millimeters 1st group

Mounting Slot Width:

11.0 millimeters 2nd group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 2nd group

Mounting Method:

Unthreaded hole 1st group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

W/resistor

Winding Operating Current:

82.0 amperes dc single component single secondary

Winding Power Rating:

10.2 kilovolt-amperes single component single secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Special Features:

In mrc cbbl resistors are variable

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0