

View Online at <https://aerobasegroup.com/nsn/5950-01-380-0936>

**Reliability Indicator:**

Not established

**Overall Length:**

410.0 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

260.0 millimeters all mounting facilities 1st center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

165.0 millimeters all mounting facilities 1st center group

**Overall Height:**

267.0 millimeters

**Overall Width:**

173.0 millimeters

**Mounting Hole Diameter:**

16.0 millimeters 1st group

**Mounting Slot Width:**

11.0 millimeters 2nd group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to six phase single component

**Transformer Winding Connection Type:**

Delta-wye

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

6 2nd group

**Mounting Method:**

Unthreaded hole 1st group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Features Provided:**

W/resistor

**Winding Operating Current:**

82.0 amperes dc single component single secondary

**Winding Power Rating:**

10.2 kilovolt-amperes single component single secondary

**Winding Operating Voltage:**

440.00 ac volts single component single primary

**Special Features:**

In mrc cbbl resistors are variable

**Terminal Type And Quantity:**

2 terminal block w/screws

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0