# NSN 5950-01-380-0962

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-380-0962

## **Reliability Indicator:**

Not established

#### Hazardous Locations/environmental Protection:

Vibration resistant and humidity resistant

## Turn Quantity:

4 single component single winding

#### Inductance Type:

Swinging

## Inductance Rating:

4.30 microhenries single component single winding and 7.00 microhenries single component single winding

## Frequency Rating:

15.75 kilohertz single component

#### Body Length:

0.335 inches

## Body Width:

0.300 inches

## Body Height:

0.335 inches

## Maximum Operating Temp:

155.0 degrees celsius

#### Winding Quantity:

1 single component

## Inclosure Type:

Fully enclosed

## Mounting Method:

Terminal single group

#### **Rating Method:**

Electrical single component single winding and winding turns single component single winding

## Winding Conductor Size:

 $0.01594 \ \text{inches}$  american wire gage single component single winding

#### Winding Operating Current:

1.7 amperes dc single component single winding

## Dc Resistance Rating In Ohms:

0.014 single component single winding

## Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5950-01-380-0962

Reactor - Page 2 of 2

Fiig: A058b0

