

View Online at <https://aerobasegroup.com/nsn/5950-01-380-9780>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and flame resistant and salt spray resistant and vibration resistant

Overall Length:

5.460 inches

Overall Height:

6.100 inches

Mounting Hole Diameter:

0.110 inches 1st group

Mounting Slot Width:

0.109 inches 2nd group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internally shielded single component

Body Width:

3.600 inches

Maximum Operating Temp:

200.0 degrees celsius

Distance Between Mounting Facility Centers:

2.500 inches 1st mounting facili type 1st center group and 2.540 inches 1st mounting facili type 1st center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 all groupings

Mounting Method:

Bracket single group and unthreaded hole single group and slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

3.0 amperes ac single component single primary

Winding Operating Voltage:

74.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0