NSN 5950-01-380-9806

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-380-9806

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and vibration resistant and humidity resistant

Turn Quantity:

24 single component 1st winding

Mounting Hole Diameter:

0.216 inches single group and 0.222 inches single group

Inductance Type:

Fixed

Inductance Rating:

21.70 microhenries single component 1st winding

Frequency Rating:

100.0 kilohertz single component

Body Length:

Between 1.985 inches and 2.015 inches

Body Width:

Between 1.985 inches and 2.015 inches

Body Height:

Between 0.570 inches and 0.600 inches

Maximum Operating Temp:

155.0 degrees celsius

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component all winding and winding turns single component all winding

Winding Conductor Size:

0.04526 inches american wire gage single component 1st winding

Winding Operating Current:

5.8 amperes dc single component 1st winding

Dc Resistance Rating In Ohms:

0.250 single component 2nd winding

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

NSN 5950-01-380-9806

Reactor - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0