

View Online at <https://aerobasegroup.com/nsn/5950-01-381-7373>

Reliability Indicator:

Not established

Overall Length:

250.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

190.0 millimeters single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

89.0 millimeters single mounting facility single center group

Overall Height:

208.0 millimeters

Overall Width:

110.0 millimeters

Mounting Slot Width:

9.0 millimeters single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

3 primary single component and 6 secondary single component

Winding Operating Current:

24.6 amperes ac single component 2nd secondary

Winding Power Rating:

2.38 k1lovolt-amperes single component single primary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0