

View Online at <https://aerobasegroup.com/nsn/5950-01-381-7729>

Reliability Indicator:

Not established

Overall Length:

164.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Width:

85.0 millimeters single mounting facility single center group

Overall Height:

155.0 millimeters

Overall Width:

100.0 millimeters

Mounting Slot Width:

7.0 millimeters single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to twelve phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

3 primary single component and 12 secondary single component

Winding Operating Current:

2.5 amperes ac single component single secondary and 2.5 amperes ac single component single secondary and 5.0 amperes ac single component single secondary and 5.0 amperes ac single component single secondary

Winding Power Rating:

435.0 volts-amperes single component single primary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single primary

Special Features:

Primary internal connection split to provide dual connection

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0