

View Online at <https://aerobasegroup.com/nsn/5950-01-381-7729>

**Reliability Indicator:**

Not established

**Overall Length:**

164.0 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

85.0 millimeters single mounting facility single center group

**Overall Height:**

155.0 millimeters

**Overall Width:**

100.0 millimeters

**Mounting Slot Width:**

7.0 millimeters single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to twelve phase single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

3 primary single component and 12 secondary single component

**Winding Operating Current:**

2.5 amperes ac single component single secondary and 2.5 amperes ac single component single secondary and 5.0 amperes ac single component single secondary and 5.0 amperes ac single component single secondary

**Winding Power Rating:**

435.0 volts-amperes single component single primary

**Winding Operating Voltage:**

115.00 ac pounds per hour wet single component single primary

**Special Features:**

Primary internal connection split to provide dual connection

**Terminal Type And Quantity:**

2 terminal block w/screws

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0