

View Online at <https://aerobasegroup.com/nsn/5950-01-381-8152>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Turn Quantity:

3 single component single winding

Mounting Hole Diameter:

0.123 inches single group and 0.133 inches single group

Inductance Type:

Swinging

Inductance Rating:

0.80 microhenries single component single winding and 1.40 microhenries single component single winding

Frequency Rating:

10.0 kilohertz single component

Body Length:

Between 0.612 inches and 0.672 inches

Body Outside Diameter:

0.870 inches

Maximum Operating Temp:

120.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Features Provided:

Tinned wire leads

Winding Conductor Size:

0.01003 inches american wire gage single component single winding

Winding Operating Current:

20.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.0038 single component single winding

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0