

View Online at <https://aerobasegroup.com/nsn/5950-01-394-4673>

Reliability Indicator:

Not established

Impedance Rating In Ohms:

125.0 single component all secondary

Frequency Rating:

50.0 hertz single component and 30.0 kilohertz single component

Maximum Transformer Power Rating:

400.0 milliwatts single component

Primary To Secondary Turn Ratio:

7.07 to 1 single component

Body Length:

0.520 inches

Body Outside Diameter:

0.750 inches

Maximum Operating Temp:

130.0 degrees celsius

Mounting Bolt Circle Diameter:

0.600 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Tinned wire leads

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 wire lead

Specification Data:

81349-mil-t-27/359 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0