

View Online at <https://aerobasegroup.com/nsn/5950-01-396-8620>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.540 inches single mounting facility single center group and 2.580 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.850 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.970 inches

Body Width:

2.300 inches

Body Height:

1.490 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

470.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Special Features:

Windings 1 through 4 are internally connected to center tap of winding no 5

Test Data Document:

77245-175614 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 pin

Specification Data:

77245-175614-101 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0