NSN 5950-01-417-2047



Reactor-transformer - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5950-01-417-2047 **Reliability Indicator:** Not established **Overall Length:** 0.700 inches **Mounting Hole Diameter:** 0.120 inches single group **Inductance Rating:** 10.00 microhenries single component single winding Frequency Rating: 100.0 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component **Winding Shielding Method:** Core grounded to inclosure single component **Overall Diameter:** 0.875 inches **Maximum Operating Temp:** 170.0 degrees celsius **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 1 single group **Mounting Method:** Unthreaded hole single group **Rating Method:** Electrical single component single winding **Winding Function And Quantity:** 1 primary single component and 2 secondary single component **Winding Operating Current:** 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 0.012 single component single winding **Winding Operating Voltage:** 8.48 ac volts single component all secondary **Terminal Type And Quantity:** 8 pin **Specification Data:** 98571-856445 manufacturers source control Shelf Life: N/a

Unit Of Measure:

NSN 5950-01-417-2047

Reactor-transformer - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A058b0