NSN 5950-01-435-5976

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-435-5976

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.300 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.300 inches single mounting facility single center group
Overall Height:
1.250 inches
Inductance Type:
Fixed
Inductance Rating:
250.00 microhenries single component single winding and 900.00 microhenries single component single winding
Frequency Rating:
35.7 kilohertz single component
Body Length:
1.660 inches
Body Width:
1.660 inches
Body Height:
1.000 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component single winding
Thread Size:
0.112 inches single group
Winding Operating Current:
1.45 amperes ac single component single winding
Dc Resistance Rating In Ohms:

Test Data Document:

95542-151-537 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

0.057 single component single winding

Unc single group

NSN 5950-01-435-5976

Reactor - Page 2 of 2



Terminal Type And Quantity:
2 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0