## NSN 5950-01-436-1100

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-436-1100
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Flame resistant and moisture resistant and salt spray resistant and vibration resistant
Turn Quantity:
8 single component single winding
Inductance Type:
Fixed
Inductance Rating:
3.06 microhenries single component single winding and 3.74 microhenries single component single winding
Frequency Rating:
55.0 kilohertz single component and 80.0 kilohertz single component
Body Length:
0.400 inches
Body Outside Diameter:
0.700 inches
Maximum Operating Temp:
144.0 degrees celsius
End Application:
F-15i
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Plug-in single group
Rating Method:
Electrical single component single winding
Winding Operating Current:
14.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.005 single component single winding
Special Features:
Requested name inductor, input filter choke
Terminal Type And Quantity:
2 pin
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-436-1100

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0