## NSN 5950-01-457-7370

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-457-7370

**Reliability Indicator:** Not established **Overall Length:** 2.380 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches single mounting facility single center group **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.500 inches single mounting facility single center group **Overall Height:** 3.130 inches **Overall Width:** 2.000 inches Frequency Rating: 50.0 hertz single component or 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group **Winding Function And Quantity:** 1 primary 4th component and 1 secondary 4th component Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.164 inches single group **Winding Operating Current:** 2.0 amperes ac single component single secondary **Winding Operating Voltage:** 115.00 ac volts single component single primary **Test Data Document:** 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 5 wire hook **Specification Data:** 

N/a

Shelf Life:

81349-mil-t-27/315 government specification

## NSN 5950-01-457-7370

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0