## NSN 5950-01-462-4956

Reactor-transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-462-4956 **Reliability Indicator:** Not established **Overall Height:** 0.635 inches **Inductance Rating:** 0.75 millihenries all components all winding **Overall Diameter:** 0.950 inches **End Application:** Mlvs e/i fscm 30003 **Inclosure Type:** Fully enclosed **Rating Method:** Electrical all components all winding **Winding Operating Current:** 1.6 amperes dc all components all winding Dc Resistance Rating In Ohms: 0.380 all components all winding **Special Features:** All units are magnetically shielded; windings may be connected series or parallel; mrc acyv, crbz and crgs are for series. Parallel ratings are acyv .1875; crbz 3.2 and crgs .095 **Test Data Document:** 81349--27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 4 wire lead **Specification Data:** 81349--27/356-45 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Yes - demil/mli

Fiig:

A058b0