

View Online at <https://aerobasegroup.com/nsn/5950-01-468-3029>

Reliability Indicator:

Not established

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.440 inches

Body Width:

4.500 inches

Body Height:

2.880 inches

End Application:

Panel control, wsd: ticonderoga class c (47)

Inclosure Type:

Fully enclosed

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

5.45 amperes ac single component single secondary

Winding Operating Voltage:

28.00 ac pounds per hour wet single component single secondary

Test Data Document:

81349-mil-prf-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 wire hook

Specification Data:

81349-mil-prf-27/319 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

Mil-std (military Standard):

Mil-prf-27 spec.